

# Time-resolved searchlight analysis of imagined visual motion using 7 T ultra-high field fMRI

Citation for published version (APA):

Emmerling, T. C., Zimmermann, J., Sorger, B., Frost, M., & Goebel, R. (2016). Time-resolved searchlight analysis of imagined visual motion using 7 T ultra-high field fMRI: Data on interindividual differences. *Data in brief*, 7, 468-471. <https://doi.org/10.1016/j.dib.2016.02.071>

## Document status and date:

Published: 01/06/2016

## DOI:

[10.1016/j.dib.2016.02.071](https://doi.org/10.1016/j.dib.2016.02.071)

## Document Version:

Publisher's PDF, also known as Version of record

## Document license:

CC BY

## Please check the document version of this publication:

- A submitted manuscript is the version of the article upon submission and before peer-review. There can be important differences between the submitted version and the official published version of record. People interested in the research are advised to contact the author for the final version of the publication, or visit the DOI to the publisher's website.
- The final author version and the galley proof are versions of the publication after peer review.
- The final published version features the final layout of the paper including the volume, issue and page numbers.

[Link to publication](#)

## General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal.

If the publication is distributed under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license above, please follow below link for the End User Agreement:

[www.umlib.nl/taverne-license](http://www.umlib.nl/taverne-license)

## Take down policy

If you believe that this document breaches copyright please contact us at:

[repository@maastrichtuniversity.nl](mailto:repository@maastrichtuniversity.nl)

providing details and we will investigate your claim.



## Data article

# Time-resolved searchlight analysis of imagined visual motion using 7 T ultra-high field fMRI: Data on interindividual differences



Thomas C. Emmerling<sup>a,b,\*</sup>, Jan Zimmermann<sup>a,b</sup>,  
Bettina Sorger<sup>a,b</sup>, Martin Frost<sup>a,b</sup>, Rainer Goebel<sup>a,b,c</sup>

<sup>a</sup> Department of Cognitive Neuroscience, Maastricht University, 6229 EV Maastricht, The Netherlands

<sup>b</sup> Maastricht Brain Imaging Center, 6229 ER Maastricht, The Netherlands

<sup>c</sup> Netherlands Institute for Neuroscience (NIN), 1105 BA Amsterdam, The Netherlands

## ARTICLE INFO

## Article history:

Received 16 December 2015

Received in revised form

20 February 2016

Accepted 26 February 2016

Available online 5 March 2016

## Keywords:

Decoding

Functional magnetic resonance imaging

Multi-voxel pattern analysis

Ultra-high field MRI

Visual mental imagery

Searchlight analysis

## ABSTRACT

Interindividual differences play a crucial role in research on mental imagery. The inherently private nature of imagery does not allow for the same experimental control that is possible in perception research. Even when there are precise instructions subjects will differ in their particular imagery strategy and, hence, show different brain activations. Here, we show results of a time-resolved searchlight analysis for 12 individual subjects who perform a visual motion imagery task. The data show the spatial and temporal extent of brain areas and time windows that allow for a successful decoding of the direction of imagined motion out of four options. Accuracy maps for six different time windows are shown for every individual subject and are made freely available on NeuroVault. These data accompany the findings in the publication “Decoding the direction of imagined visual motion using 7 T ultra-high field fMRI” (Emmerling et al., 2016) [1].

© 2016 The Authors. Published by Elsevier Inc. This is an open access article under the CC BY license

(<http://creativecommons.org/licenses/by/4.0/>).

## Specifications Table

Subject area Psychology

DOI of original article: <http://dx.doi.org/10.1016/j.neuroimage.2015.10.022>

\* Corresponding author at: Department of Cognitive Neuroscience, Faculty of Psychology and Neuroscience, Maastricht University, Oxfordlaan 55, 6229 EV, P.O. Box 616, 6200MD Maastricht, The Netherlands. Fax: +31 433884125.

E-mail address: [thomas.emmerling@maastrichtuniversity.nl](mailto:thomas.emmerling@maastrichtuniversity.nl) (T.C. Emmerling).

<http://dx.doi.org/10.1016/j.dib.2016.02.071>

2352-3409/© 2016 The Authors. Published by Elsevier Inc. This is an open access article under the CC BY license (<http://creativecommons.org/licenses/by/4.0/>).

More specific sub- ject area	<i>Cognitive Neuroscience</i>
Type of data	<i>Maps</i>
How data was acquired	<i>7 T functional magnetic resonance imaging</i>
Data format	<i>Analyzed</i>
Experimental factors	<i>Significance maps from searchlight multi-voxel pattern analysis (MVPA) that were transformed into MNI-space</i>
Experimental features	<i>Decoding of four different directions of imagined visual motion throughout the cortical ribbon in 12 subjects</i>
Data source location	<i>Maastricht, Netherlands</i>
Data accessibility	<i>Data is within this article</i>

**Value of the data**

- Time-resolved significance maps show spatial and temporal differences between 12 subjects.
- Additional behavioral data from the original publication provide information about individual strategies and performance in widely used imagery questionnaires.
- Maps are available on NeuroVault.org making comparisons with other studies easier.

**1. Data**

We show data of a time-resolved searchlight analysis for 12 individual subjects performing a visual motion imagery task. In each searchlight sphere a multi-voxel pattern analysis (MVPA) is performed to decode four different directions of imagined motion. This is done for six different but overlapping time windows with respect to the onset of an imagery trial. The resulting volumetric maps show p-values for FDR-corrected Chi-square tests of the confusion matrices of each searchlight sphere. Maps were uploaded to NeuroVault.org (<http://neurovault.org/collections/961>).

**2. Experimental design, materials and methods**

*2.1. Subjects*

15 healthy fMRI-experienced subjects (six females; age:  $27.4 \pm 6.3$  years) volunteered in the original study [1]. Data from 12 subjects were analyzed based on exclusion criteria described in Emmerling et al. [1].

*2.2. Procedure*

Subjects attended three training sessions and one scanning session. The training was designed to practice the experimental task and more specifically a stable visual motion imagery. Details on the training procedure [p. 62; 1], the individual used imagery strategies [Table 1; 1], and behavioral results from the training sessions [Fig. 5; 1] are described in Emmerling et al. [1].

Subjects were pseudo-randomly assigned to one of two groups and had to imagine dots that moved in one of four directions (group 1: left, right, up, and down; group 2: four diagonal motion directions).

### 2.3. Additional behavioral data

All subjects filled in the Vividness of Visual Imagery Questionnaire [VVIQ; 2] and the Object-Spatial Imagery and Verbal Questionnaire [OSIVQ; 3]. For procedural details, analyses, and results please see the original publication [Figs. 3 and 4; 1].

For information on the experimental task, MRI acquisition, and imaging data preprocessing please refer to the corresponding sections in the original publication [p. 62–65; 1].

### 2.4. Searchlight analysis

Each experimental run was z-scored to eliminate signal offsets and variance differences between runs. The data were split into training and testing datasets. We employed a leave-one-run-out splitting procedure to be able to cross-validate the classification performance. To assess the spatial distribution of brain areas involved in the mental imagery task we performed a searchlight analysis [4]. A sphere with a radius of 4 voxels was moved through the cortical ribbon (so that the spheres central voxel always lay within  $-1$  mm to  $+3$  mm from the grey/white matter segmentation border) and defined a feature set of 257 voxels (4 voxel radius). For each voxel within each sphere and each trial we extracted the average of 6 s (3 TRs) as features. Averages were computed in six different but overlapping time windows starting at  $-2$ , 0, 2, 4, 6, and 8 s (*i.e.*  $-1$ , 0, 1, 2, 3, and 4 TRs) with respect to the trial onset. The extracted features were then used for an one-vs-one 4-class classification (predicted classes were chosen based on the maximum number of votes in all binary classifications) using a linear support vector machine [SVM; LIBSVM implementation in PyMVP; 5]. The resulting classification accuracies were tested for significance by means of FDR-corrected Chi-square tests of the confusion matrix.

### 2.5. MNI space transformation

Individual anatomies were transformed to MNI-ICBM 152 space [6] using BrainVoyager 20.0 and the ICBM 452 template [7]. The individual significance maps for the six different time windows were resampled to a resolution of  $1 \times 1 \times 1$  mm<sup>3</sup> voxel size and transformed into MNI space using the individual transformation matrices obtained in the previous step. The resulting maps were named according to the subject (“S01” through “S12”) and the time window (“\_shift\_1” through “\_shift\_4”) and uploaded to NeuroVault.org (<http://neurovault.org/collections/961/>).

## Acknowledgments

This work was supported by the European Research Council (ERC) under European Union's Seventh Framework Programme FP7/2007–2013/ERC (Grant Agreement Number 269853). We would like to thank Franziska Dambacher, Felix Dücker, Tom de Graaf, Lars Hausfeld, and Giancarlo Valente for their help.

## Appendix A. Supplementary material

Supplementary data associated with this article can be found in the online version at <http://dx.doi.org/10.1016/j.dib.2016.02.071>.

## References

- [1] T.C. Emmerling, J. Zimmermann, B. Sorger, M.A. Frost, R. Goebel, Decoding the direction of imagined visual motion using 7 T ultra-high field fMRI, *Neuroimage* 125 (2016) 61–73. <http://dx.doi.org/10.1016/j.neuroimage.2015.10.022>.

- [2] D.F. Marks, Visual imagery differences in the recall of pictures, *Br. J. Psychol.* 64 (1973) 17–24. <http://dx.doi.org/10.1111/j.2044-8295.1973.tb01322.x>.
- [3] O. Blazhenkova, M. Kozhevnikov, The new object-spatial-verbal cognitive style model: theory and measurement, *Appl. Cogn. Psychol.* 23 (2009) 638–663. <http://dx.doi.org/10.1002/acp.1473>.
- [4] N. Kriegeskorte, R. Goebel, P. Bandettini, Information-based functional brain mapping, *Proc. Natl. Acad. Sci. USA* 103 (2006) 3863–3868. <http://dx.doi.org/10.1073/pnas.0600244103>.
- [5] C.-C. Chang, C.-J. Lin, Libsvm, *ACM Trans. Intell. Syst. Technol.* 2 (2011) 1–27. <http://dx.doi.org/10.1145/1961189.1961199>.
- [6] J. Mazziotta, A. Toga, A. Evans, P. Fox, J. Lancaster, K. Zilles, et al., A probabilistic atlas and reference system for the human brain: International Consortium for Brain Mapping (ICBM), *Philos. Trans. R. Soc. B: Biol. Sci.* 356 (2001) 1293–1322. <http://dx.doi.org/10.1098/rstb.2001.0915>.
- [7] J. Mazziotta, A. Toga, A. Evans, P. Fox, J. Lancaster, K. Zilles, et al., A four-dimensional probabilistic atlas of the human brain, *J. Am. Med. Inform. Assoc.* 8 (2001) 401–430. <http://dx.doi.org/10.1136/jamia.2001.0080401>.